



Formerly Known As: PANOLIN EP GEAR SYNTH

Shell PANOLIN S4 Gear 220

- Extended Life
- Readily Biodegradable

Industrial gear oil - readily biodegradable, saturated synthetic esters

Shell PANOLIN S4 Gear is a synthetic fluid for use in gearing applications such as marine propulsion drives, thrusters and controllable pitch propellers, high-performance and readily biodegradable lubricant, based on saturated synthetic esters for industrial gear drives.

High-Performance Biodegradable Lubricants

Performance, Features & Benefits

• Increased Wear Protection

Carefully selected additives provide advanced wear protection over a wide range of conditions, ensuring long component life.

• Maintaining system efficiency

Shell PANOLIN S4 Gear Oil has a high viscosity index helps protect components over a wide temperature range, making this a true multigrade gear oil.

The low pour point and cold flow characteristics provide protection and performance even in cold climates.

• Lower Environmental Impact

Recommended for use in environmentally sensitive areas - offers reduced impact of leak or accidental spillage into the environment compared to conventional mineral oils.

Readily biodegradable, biodegraded by over 60% after 28 days in the OECD 301 B carbon dioxide evolution test. Low Ecotoxicity, classified as 'not harmful' when tested as water-accommodated fractions (WAFs) according to OECD and EPA test guidelines. Tested to Industry Standard by 3rd Party Lab, all Shell PANOLIN products are tested against OECD 202.

Main Applications



Specifications, Approvals & Recommendations

- ZF TE-ML 04M
- Biodegradable OECD 301B >60%
- FZG load stage 12 (DIN 51354)

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Compatibility & Miscibility

- It is strongly recommended that an oil sample is taken from the system following changeover and analysed via the Shell Rapid Lubricants Analysis service to confirm the new fluid charge is fit for use.

• Fluid Compatibility

Shell PANOLIN Fluids are miscible with mineral oils. However, in order to ensure that the environmental properties and performance of Shell PANOLIN Fluids are maintained, the system should be drained and flushed thoroughly when changing fluids.

Typical Physical Characteristics

Properties			Method	Shell PANOLIN S4 Gear 220
Kinematic Viscosity	@40°C	mm ² /s	ASTM D445	220
Pour Point		°C	ASTM D97	-41
Flash Point		°C	ASTM D92	300
Density	@15°C	kg/m ³	ASTM D4052	923

These characteristics are typical of production, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <http://www.epc.shell.com>.

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

- **Advice**

Advice on applications not covered here may be obtained from your Shell Representative.